

POWERED BY **Dialog**

Prepreg for laminate formation for printed circuit for high migration resistance - comprises glass cloth comprising glass fibres with low coefft of thermal expansion and high coating build-up of silane finishing agent with polyepoxy resin
Patent Assignee: SHIN KOBE ELECTRIC MACHINERY

Patent Family

Patent Number	Kind	Date	Application Number	Kind	Date	Week	Type
JP 8092394	A	19960409	JP 94231897	A	19940927	199624	B

Priority Applications (Number Kind Date): JP 94231897 A (19940927)

Patent Details

Patent	Kind	Language	Page	Main IPC	Filing Notes
JP 8092394	A		6	C08J-005/24	

Abstract:

JP 8092394 A

A prepreg (I) is prepd. by impregnating the base material of glass cloth with a thermoset resin followed by drying. The glass cloth comprises glass fibres which have a coefft of thermal expansion of less than 4 ppm/deg. C and the coating build-up of a finishing agent on them of more than 0.15 wt. %, pref. more than 0.2 wt. %, to intensify the affinity with the thermoset resin. Also claimed is a laminate (II) prepd. from (I).

USE - (II) is used for printed circuit laminates.

ADVANTAGE - (II) has a low coefft. of thermal expansion and a high migration resistance.

Dwg.0/1

Derwent World Patents Index

© 2003 Derwent Information Ltd. All rights reserved.

Dialog® File Number 351 Accession Number 10739239